






Nosnosti lanových viazacích prostriedkov s nalisovanými objímkami podľa EN 13414-1 a EN 13411-3

Prevedenie	1-pramenný záves	2-pramenný záves		3- a 4-pramenný záves		Nekonečné lano	
							
Uhol sklonu	0°	0° < β < 45°	45° < β < 60°	0° < β < 45°	45° < β < 60°	0°	
Priemer lana mm	Hranica pracovného zaťaženia WLL (nosnosť závesu) v kg pre laná konštrukcie 6x37M-FC, s pevnosťou drôtov 1770 N/mm ²						
3	86	121	86	181	129	173	
4	153	215	153	322	230	307	
5	240	335	240	503	359	479	
6	345	483	345	725	518	690	
7	470	657	470	986	704	939	
8	613	859	613	1 288	920	1 227	
9	776	1 087	776	1 630	1 164	1 553	
10	958	1 342	958	2 013	1 438	1 917	
11	1 160	1 624	1 160	2 435	1 739	2 319	
12	1 380	1 932	1 380	2 898	2 070	2 760	
13	1 620	2 268	1 620	3 401	2 430	3 239	
14	1 878	2 630	1 878	3 945	2 818	3 757	
15	2 156	3 019	2 156	4 528	3 235	4 313	
16	2 454	3 435	2 454	5 152	3 680	4 907	
18	3 105	4 347	3 105	6 521	4 658	6 210	
20	3 834	5 367	3 834	8 051	5 750	7 667	
22	4 639	6 494	4 639	9 741	6 958	9 277	
24	5 520	7 729	5 520	11 593	8 281	11 041	
25	5 990	8 386	5 990	12 579	8 985	11 980	
26	6 479	9 070	6 479	13 605	9 718	12 958	
28	7 514	10 519	7 514	15 779	11 271	15 028	
30	8 626	12 076	8 626	18 114	12 938	17 251	
32	9 814	13 740	9 814	20 609	14 721	19 628	
34	11 079	15 511	11 079	23 266	16 619	22 158	
36	12 421	17 389	12 421	26 084	18 631	24 842	
38	13 839	19 375	13 839	29 063	20 759	27 679	
40	15 334	21 468	15 334	32 202	23 002	30 669	
42	16 906	23 669	16 906	35 503	25 359	33 812	
44	18 555	25 976	18 555	38 965	27 832	37 109	
46	20 280	28 392	20 280	42 587	30 420	40 560	
48	22 082	30 914	22 082	46 371	33 122	44 163	
50	23 960	33 544	23 960	50 316	35 940	47 920	
52	25 915	36 281	25 915	54 422	38 873	51 830	
54	27 947	39 126	27 947	58 689	41 920	55 894	
56	30 055	42 078	30 055	63 116	45 083	60 111	
58	32 241	45 137	32 241	67 705	48 361	64 481	
60	34 502	48 303	34 502	72 455	51 754	69 005	
62	36 841	51 577	36 841	77 366	55 261	73 682	
64	39 256	54 959	39 256	82 438	58 884	78 512	

